


INTI 152B-L02X1K-03 Solar Surface Mounted INTI 1 Beam Steady IP68 LED SMD 0.34W CRI80 Grey



Inti solar wall light family is made of aluminum with IP68, available in different variants SMD LED and AMBER SMD LED. It is installed on the ground. It is recommended to illuminate the passage areas of large outdoor surfaces.

GENERAL DATA

Category	Surface
Family	Inti
Finish	[03] Grey
Location	Outdoor
Installation	Floor
Body material	Aluminum
Diffuser material	Transparent polycarbonate
Reflector material	Polycarbonate
ETIM class	EC000481
EAN	8433264103842

LIGHT SOURCES AND BEAMS

Sources	LED SMD 0.337W CRI80
Total flux	0 lm

TECHNICAL DATA

Dimensions	Width x Height x Depth (mm): 110 x 30 x 90
IP	IP68
IK	10
Dinamic pressure	3,500.0 Kg
Protection class	Class III
Input voltage	3.15V DC V
Output current	3 mA
Battery charge time	8.0 h
Battery autonomy	12.0 h
Operating temperature range	-40 - 70 °C
Lifetime	50,000 h
LED lifetime L	80
LED lifetime B	20
Weight	0.4 Kg
Cable outlets	1
ECORAE category I	LED-A

NOTES

Loading time: 3/8h
Full load duration: 16h
Sensor level: 150/350 lux
Thermal amplitude: -25° +60 °C
Luminaire suitable for installation in environments with saline atmosphere

INTI 152B-L02X1K-03 Solar Surface Mounted INTI 1 Beam Steady IP68 LED SMD 0.34W CRI80 Grey

PRODUCTS OF THE SAME FAMILY



Inti 1Beam
Flashing



Inti 2Beam
Flashing



Inti 2Beam Steady