

**TM TECHNOLOGIE**  
emergency & evacuation lighting

**TM.ONTEC S**

IP 44 IP 65 LED 1h/3h 850 °C

210 ÷ 250 V AC  
50 / 60 Hz  
186 ÷ 254 V DC  
20 ÷ 57 V DC

0.7 m EAC CNBOP-PIB CE

**A1** **A2**

**B1** **B2**

**A3** **B3**

! ±1 [mm]

! \*B1, B2, B3 \*A2, B2

**1** CBA, CBM, D2, D2R, DA, D3, D3R, DL, CBM 48

TM-PROG

CBx≤10mm / Dx≤10mm

1.1 CBx≤25mm / Dx≤40mm

**2** A1, A2, B1, B2  
C1-C2  
F1-F2  
W1-W2

**3** A1, A2, B1, B2  
3.1a 1.3 → 1.4a → 1.5a

3.2\* 3.3a 3.4a 3.5a 3.6a 1.12\* → 1.13a → 1.14a

**A3, B3**  
3.1c 1.3 → 1.4c → 1.5c → 3.2\*

**4** \*ST/AT/DT/D2/D2R/DA/D3/D3R/DL  
A1, A2, B1, B2  
4.1a 1.3 → 1.4a → 1.5a  
A3, A3  
4.1c 1.3 → 1.4c → 1.5c

LiFePO4/C 3.2V 1.5Ah

Ni-Cd 3.6V 1.5Ah (2.5Ah)

LiFePO4/C 6.4V 1.5Ah (3.0Ah) 4.5Ah

**A1, A2** 4.7a 1.12\* → 1.13a → 1.14a  
**A3, B3** 4.7c 1.12\* → 1.13c → 1.14c

ONTEC S	M	NM	CB	ONTEC S	M1	ONTEC S	CBA	ONTEC S	CBA	CB+, CBM
t. [°C]	90	77	97,5	t. [°C]	85	t. [°C]	97,5	t. [°C]	80°C	95°C

ONTEC S	6 LED	7 LED	14 LED	21 LED	ONTEC S	M1 24(48)V CB	ONTEC S	M(C)(W)(F)1U
t. [°C]	87	85	71	59	t. [°C]	85	t. [°C]	55

ONTEC S	1 LED	2 LED	ONTEC S	E1P (14 LED)	ONTEC S	CB 24/48, CBM 48
t. [°C]	85	95	t. [°C]	50	t. [°C]	110°C

TM TECHNOLOGIE Sp. z o.o., Morawica 355, 32-084 Morawica, gm. Liszki, Poland, tel.: +48 12 444 60 60, fax: +48 12 350 57 34, www.tmtechnologie.pl



