

OCULUS L

Indoor lighting fixtures, environmentally friendly SMD chips.
Good heat dissipation structure design.
Elegant appearance and concise.



Luminaire

Product type

Material

Colour

Spotlights

Diecast Aluminum

Sandy black , Sandy white ,
Matte silver , Matte Brass ,
Matte Bronze



OCULUS-L

Installation

Environment

IP

Mounting

Indoor

20

Recessed

Light Source

Luminous flux

Power

Typical voltage

CRI

CCT


1432Lm

18W

36V

90

2700K / 3000K / 4000K



Optics

Light controller type

Lens: 20°/25°/36°/50°

Driver

Input voltage(V)

Power Factor

Output current

Dimming Type

220-240V/100-277V/100-240V


0.5C/0.9C/0.95C

450mA


On/Off/DALI DT6/0-10V/Triac



OCULUS-L-12B-S1



OCULUS-L-12B-S2



OCULUS L

Indoor lighting fixtures, environmentally friendly SMD chips.
Good heat dissipation structure design.
Elegant appearance and concise.



Luminaire

Product type

Material

Colour

Spotlights

Diecast Aluminum

Sandy black , Sandy white ,
Matte silver , Matte Brass ,
Matte Bronze

Installation

Environment

IP

Mounting

Indoor

20

Recessed

Light Source

Luminous flux

Power

Typical voltage

CRI

CCT

1047~1301Lm

18W

36V

90

2700K-6000K

Optics

Light controller type

Lens: 20°/25°/36°/50°

Driver

Input voltage(V)

Power Factor

Output current

Dimming Type

220-240V


0.9C/0.5C

450mA/350mA


DALI DT8/Bluetooth+2.4G Dimming
and color adjustment




OCULUS-L



OCULUS-L-12B-S1



OCULUS-L-12B-S2



RE-STAR-1801

Indoor lighting fixtures, environmentally friendly SMD chips.
Good heat dissipation structure design.
Elegant appearance and concise.



Luminaire

Product type

Material

Colour

Spotlights

Diecast Aluminum

Sandy black , Sandy white ,
Matte silver , Matte Brass ,
Matte Bronze

Installation

Environment

IP

Mounting

Indoor

20

Recessed

Light Source

Luminous flux

Power

Typical voltage

CRI

CCT

1082Lm

18W

36V

90

1800K-5000K

Optics

Light controller type

Lens: 20°/25°/36°/50°

Driver

Input voltage(V)

Power Factor

Output current

Dimming Type

220-240V


0.9C

350mA


DALI DT8




OCULUS-L



OCULUS-L-12B-S1



OCULUS-L-12B-S2



OCULUS L

Indoor lighting fixtures, environmentally friendly SMD chips.
Good heat dissipation structure design.
Elegant appearance and concise.



Luminaire

Product type

Material

Colour

Spotlights

Diecast Aluminum

Sandy black , Sandy white ,
Matte silver , Matte Brass ,
Matte Bronze

Installation

Environment

IP

Mounting

Indoor

44/65

Recessed

Light Source

Luminous flux

Power

Typical voltage

CRI

CCT

1352Lm

18W

36V

90

2700K / 3000K / 4000K

Optics

Light controller type

Lens: 20°/25°/36°/50°

Driver

Input voltage(V)

Power Factor

Output current

Dimming Type

220-240V/85-265V


0.9C

350mA


On/Off



OCULUS-L



OCULUS-L-12B-S1



OCULUS-L-12B-S2

